JACKSON COUNTY FAIR

2022 DEMO RULES

MINI- CAR

EVENT RULES DISCLAIMER

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events, all participants are deemed to have complied with these rules. NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM PUBLICATIONS OF OR COMPLIANCE WITH THESE RULES AND OR REGULATIONS. They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator, or official.

The race director shall be empowered to permit reasonable and appropriate deviation from any of the specifications herein or impose any further restrictions that in his/her opinion does not alter the minimum acceptable requirements. NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM SUCH ALTERATION OF SPECIFICATIONS. Any interpretation or deviation of these rules is left to the discretion of the officials. Their decision is final.

- Any front wheel drive vehicle 1980 & newer (No full-size cars or full frames)
- All cars MUST have a roof sign visible.

GENERAL CAR PREP & SAFETY

- 1. Strip all flammable materials from car. Dash may stay in car.
- 2. Gas Tank may be left in factory position as long as it is mounted in front of rear axle. Please check factory straps for security. Prefer you leave factory gas tank under vehicle. Gas tank may be moved to back seat area. If mounted to cage must be a minimum of a 4-inch gap to any surrounding sheet metal. Must be SECURELY mounted & covered. Absolutely NO Milk crates

to hold down batteries or gas cans!!! No bungee cords as tie downs!! Safety first!!

- 3. Electrical fuel pump (On/Off) switch must be clearly marked.
- 4. Front windshield must have bar, chain or wire to prevent hood from entering driver's area. From windshield to firewall/dash cowl only.
- 5. Battery must be moved to front floorboard area securely mounted and covered. One battery only.
- 6. Completely remove air bag assembly. No paint or spray foam allowed on frame.
- 7. Absolutely no spray foam around radiator or on frame. Wires and ECM ok.

BODY

- 1. Driver's door must be painted white & may be wired, chained, or welded solid and/or may have a steel driver's door skin securely fastened. All other doors welded (3 spots on vertical door seam, 3" square plates), or chained or wired in 3 spots only.
- 2. You MUST have a mandatory door plate if you do not have a cage.
- 3. Door plate must be bolted or welded on securely, no more than 6" past door seams.
- 4. You may wire top of doors to top of car. One spot per door/window opening 3 wraps max or (1) 3"x 3".
- 5. May weld washer for wire for hood, trunk, and doors. May be no bigger than 2 ½" OD
- 6. Trunk lid, hatch, gate & hood may be wired shut in 6 places. 2 spots only on front of hood and not in front of radiator.
- 7. 10" hole in hood and trunk for inspection.
- 8. Creasing allowed. Quarters must stay vertical.
- 9. Must run factory drive line, Gas & Brake pedals, Steering column, and shifter!
- 10. Headers are allowed, but not reinforce the car in any way.

BUMPER

- 1. Factory car bumper or you can change bumper to any stock automobile CAR bumper. No loaded or Chrysler pointy bumpers allowed. DEC and SMW 1/8" bumpers allowed. Call to get bumpers approved.
- 2. Bumpers may be welded on.
- 3. You may seam welded bumpers.
- 4. You may weld a plate to the bumper as long as the plate is no more than 1" wider than the frame width and height.
- 5. Bumper may be no wider than the width of front tires.
- 6. Crush boxes may be cut, but no further back than core support.
- 7. Do not alter factory frames.
- 8. You may use a 4x4" or 2x6" flat tube as a bumper. No points allowed.
- 9. HONDA'S ONLY- Can go 1" past core support. 4" long max, no thicker than 1/8", and 3x3" max diameter.

CAGE

- 1. A 4-bar floating cage allowed around driver's compartment.
- 2. Driver's door plate allowed from cage to rocker (door seam to door seam). Driver's door ONLY.
- 3. No bigger than 4" x 4" square tube.
- 4. Side bars no farther back than 6" behind driver's seat.
- 5. No down legs.
- 6. Roll over bar may extend off cage vertically. Do not lean back.
- 7. If you don't have a cage, then a door plate/bar is Mandatory.
- 8. Cage can be inside the door no more than 1" past inside door seam.

SUSPENSION

1. Factory suspension, no changes allowed, MUST bounce!

TIRES/WHEELS

1. Any wheel and tire.

"IF IT DOESN'T SAY YOU CAN, THEN YOU CAN'T."!!!!

Drivers only allowed in inspection area; no other crew allowed. You will pre-pay before inspection, If, your car does not pass inspection NO Refunds!

Drivers must wear DOT helmet, eye protection, long pants, long sleeve shirt and closed toed shoes. Fire suits are always recommended, but not required. Helmets stay on the entire time in car. Only get out of car if told ok to do so. Drivers must make an aggressive hit every 60 seconds.

Inspection will start approximately 3 hours prior to event, please be on time. Inspection closes 1 hour prior to event start time. NO Exceptions!!!

This is a beginner class intended for fun. Doing more to your car will be subject to disqualification. Inspector's decisions are final.

JACKSON COUNTY FAIR
RACE DIRECTOR
DOUG ASBURY

812.525.9941